



# Technical Data Sheet

# **Aluminum Metal Sputtering Target**

Product ID: 1300ST001 - 1300ST028

 Formular:
 Al
 Molecular weight:
 26.98 g/mol

 CAS No.:
 7429-90-5
 EINECS No.:
 231-072-3

Color: Silver

**Description:** Our aluminum target has a typical purity of 4N, 4N5, 5N, 5N5 or 6N and can be


customized in different sizes as needed. It features high electrical conductivity,

excellent corrosion resistance, and good thermal stability.

**Application:** Semiconductor industry, optical coatings, thin-film batteries, electronic

components, and decorative coatings.

Product Image:



#### 1. Sizes

Product ID	Formular	Particle Size	
1300ST001	AI (99.99%)	Ø 25.4 mm x 3.175 mm	
1300ST011	AI (99.995%)	Ø 50.8 mm x 6.35 mm	
1300ST015	AI (99.999%)	Ø 76.2 mm x 3.175 mm	
1300ST021	AI (99.9995%)	Ø 101.6 mm x 3.175 mm	
1300ST028	AI (99.9999%)	Ø 152.4 mm x 6.35 mm	
1300ST4NDZ	AI (99.99%)	Customized	
1300ST4N5DZ	AI (99.995%)	Customized	
1300ST5NDZ	AI (99.999%)	Customized	
1300ST5N5DZ	AI (99.9995%)	Customized	
1300ST6NDZ	AI (99.9999%)	Customized	



Tel: 0049 1626484175

### 2. Chemical compositions

	Metal impurities (ppm)					
Typical Value Purity	Si	Ti	Fe	Cu	Zn	
99.99%	≤ 30	≤ 20	≤ 30	≤ 50	≤ 20	
99.995%	≤ 15	≤8	≤ 15	≤ 35	≤ 8	
99.999%	≤ 2.5	≤ 1.0	≤ 2.5	≤ 4.0	≤ 1.0	
99.9995%	≤ 2.5	≤ 1.0	≤ 2.5	≤ 2.8	≤ 0.9	
99.9999%	≤ 0.2	≤ 0.1	≤ 0.1	≤ 0.2	≤ 0.05	

Note: The purity values shown are calculated by subtracting the sum of selected measured elemental impurities from 100%. These values do not represent the result of a full elemental analysis.

### 3. Packaging

Carton/wooden box outer bag. Double vacuum inner bag.

#### 4. Period of Validity

It is recommended to use this product within 12 months. If it is overdue, the product quality status should be re-evaluated.

## 8. Handling and Storage

When using, wear protective gloves to avoid direct contact, oxidation, or contamination.

Stored in a dry, sealed container, avoiding moisture and contact with acidic or oxidizing substances.

#### **Contact Us**

Website:www.vimaterial.de Email: info@vimaterial.de Tel: 0049 1626484175

Add: Begener Straße 14., 30625 Hannover, Niedersachsen, Germany.