

Technical Data Sheet

Titanium Aluminum Carbide Powder

Product ID: 22130600PD001

Formular: Ti_3AlC_2

Molecular weight: 194.6 g/mol

CAS No.: 196506-01-1

EINECS No.: /

Color: Gray-black

Description: Our Ti_3AlC_2 powder typically has a purity of over 99%. It is a MAX-phase ceramic material with high electrical conductivity, high thermal conductivity, excellent heat resistance, and oxidation resistance.

Application: High-temperature structural materials, electronics and energy storage, coating materials, lubrication materials, etc.

Product

Image:



1. Sizes

| Product ID | Formular | Particle Size |
|---------------|---------------------------------|---------------|
| 22130600PD001 | Ti_3AlC_2 (99%) | -200 Mesh |
| 22130600PDDZ | Ti_3AlC_2 | Customized |

2. Chemical compositions

| Element Typical Value Purity | Metal impurities (wt%) | | | | | |
|---------------------------------------|------------------------|-------|------|-------|------|------|
| | Zn | Cu | Mg | Fe | Mn | Si |
| 99% | ≤0.02 | ≤0.03 | ≤0.1 | ≤0.15 | ≤0.1 | ≤0.1 |

3. Packaging

Bottle/Bag.

Double vacuum packed.

4. Period of Validity

It is recommended to use this product within 12 months. If it is overdue, the product quality status should be re-evaluated.

5. Handling and Storage

When using, wear protective equipment (such as gloves, goggles, and a dust mask) to avoid inhalation of dust or skin contact.

Store in a dry, sealed environment, away from strong acids, strong oxidizers, and moisture.

Contact Us

Website: www.vimaterial.de

Email: info@vimaterial.de

Tel: 0049 1626484175

Add.: (Warehouse) Mannheimer Straße 14., 30880 Laatzen, Niedersachsen, Germany.

(Office) Begener Straße 14., 30625 Hannover, Niedersachsen, Germany.