

Technical Data Sheet

Zinc Sulfide Pellets

Product ID: 301600PL001**Formular:** ZnS**Molecular weight:** 97.46 g/mol**CAS No.:** 1314-98-3**EINECS No.:** 215-251-3**Color:** White

Description: Our zinc sulfide pellets have a typical purity of $\geq 99.99\%$ and can be customized in different sizes as needed. They feature a high refractive index, excellent optical properties, and good chemical stability.

Application: Infrared optics, fluorescent materials, coatings, and the electronics industry.

Product**Image:**

1. Physical Properties

Product ID	Formular	Size
301600PL001	ZnS (99.99%)	Ø 10 mm x 6 mm
301600PLDZ	ZnS (99.99%)	Customized

2. Chemical compositions

Element Typical Value Purity	Metal impurities (ppm)				
	Fe	Al	Pb	Cu	Mn
99.99%	≤ 20	≤ 25	≤ 10	≤ 5	≤ 5

Note: The purity values shown are calculated by subtracting the sum of selected measured elemental impurities from 100%. These values do not represent the result of a full elemental analysis.

3. Packaging

Bottled/bagged.

Double vacuum packed.

Customized according to customer requirements.

4. Period of Validity

It is recommended to use this product within 12 months. If it is overdue, the product quality status should be re-evaluated.

5. Handling and Storage

When using, wear protective gloves, safety goggles, and appropriate respiratory protection to avoid dust inhalation or skin contact.

Stored in a dry, sealed container in a well-ventilated environment, avoiding moisture and contact with acidic substances.

Contact Us

Website: www.vimaterial.de

Email: info@vimaterial.de

Tel: 0049 1626484175

Add: Begener Straße 14., 30625 Hannover, Niedersachsen, Germany.